	•		4		1		3	47		,		ı		1				
	THE II	NFORMATION	ON THIS DR.	AWING IS THE	PROERTY OF	CELESTRA, IS	3	CELESTRA	2 WIRE SIZE		BOLT	I A	В	C		ID	ì	
		OSED IN CON			REPRODUCED	, USED OR		CAT.NO	CODE	FLEX	SIZE	±0.06	MIN	±0.04	R	±0.01		
							_	WP0856-009	8 AWG	23 Navy #8 Weld 37/24 = 14.9 kcmil #6 SOL	5/16	1.19	0.49	0.45				
D																	D	
	N	IOTE:		DIMENSION CIFIED.	IS ARE IN IN	CHES UNLES	S OTHERWISE		Color coded marking									
			LIS	ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.					Bolt Size									
_	1		OTH				P HOLE UNLESS OF THE CAT.NO.	-	HU A B									
	N	MATERIAL:	HIG	H CONDUCT	TIVITY WRO	JGHT COPPE	R											
С	F	INISH:	SPE	CIFED PLAT	ΓE PER MIL -	SS OTHERWIS T -16366. FOR SILVER.	SE	]-		B	-						С	
-	INSTALLATION GUIDE DIE CODE = 21 DIE COLOR = Red  R Inspection Hole													$\leftarrow$				
В		c (LISTE	)	<b>.</b>	IEBS	3 Roll	<b>(</b> (		Bevele	d entry	_		6				В	
		WIRE CONN	ECTOR															
_	1																_	
									HUY www.huyaco	A	ELES '6. Hua Panyu [	incun	Rd. Zh	nongci	ın Tow	'n.		
Α									WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									
	00	0 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					MATERIAL HIGH-CONDU WROUGHT CO	CTIVITY PRT. NO. DPPER WP08	356-009	S	CALE N		ID ANGLE P	ROJECTION				
1	REV	DATE	DWN	СНК		DESCR	IPTION	ECN	FINISH ELECTRO TIN	51110 110	86-cp00	63	NIIT	CH +	<b>(</b>	$\exists$		
			4				3	$\triangle$	2	-				1				