	-	4	1	2	+				1		1				
			 IE PROERTY OF CELESTRA		CELESTRA WIRE SIZE			BOLT	A	В	С		ID		
		NFIDENCE AND NOT TO B FFOR WHICH FURNISHED	E REPRODUCED, USED OR		CAT.NO	CODE	FLEX 1325/24 = 535	SIZE	±0.06	MIN	±0.04	R	±0.01		
					DA7158-260	700 kcmil	kcmil 427/.0342	5/8	3.48	1.33	1.84	2.29	0.97		
D	NOTE:	1. ALL DIMENSIC SPECIFIED. 2. ALL DA,DB,LA LISTED BY "UI ON CODE WIF PRE-FIX CAT.I OTHERWISE SWITH "P".	Color coded marking Bolt Size									D			
_	FINISH:		CTIVITY WROUGHT CO				В	-							
С		SPECIFED PL	ATE PER MIL - T -16366 O.WITH "SP" FOR SILV	A									С		
B	INSTALLATION DIE CODE = DIE COLOR :	99 = Pink	IEBS ³	(€		R Bevele				6				⊕ В	
						HUY	A ® C	ELES							
А											ncun Rd. Zhongcun Town. Dist. Guangzhou 511495.				
				WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE											
	00 01-Dec-25	Ruby Feng Sinia Qiu	Celestra S	tandards Spec. Initialed.		MATERIAL HIGH-CONDU WROUGHT CO	DPPER DA71	58-260		CALE N7		RID ANGLE PF	ROJECTION		
1	REV DATE	DWN CHK	DES	SCRIPTION	ECN	FINISH ELECTRO TIN I	PLATE DWG. NO. 1	86-cp06	47 U	IN:	СН	⊕ £	\Box		
		4		3	\triangle	2					1				
					1										