		1		1		3	+	2			1		1			
l		THE INFORMATION ON THIS DRAWING IS THE PROE DISCLOSED IN CONFIDENCE AND NOT TO BE REPRO					CELESTRA	WIRE	SIZE	BOLT	A	В	С	R	ID	
	DISLOSED EXC			EPRODUCED, USED (	OK		CAT.NO DA7558-241	CODE 750kcmil	FLEX 1325/24 = 646	SIZE 5/8	±0.06	MIN 1.58	±0.04	2.37	±0.01	
							DA7556-241	7 SUKCITIII	kcmil	5/6	3.01	1.56	1.94	2.37	1.06	
D	NOTE:	SPE	ECIFIED.	S ARE IN INCHES		Color coded marking  Bolt Size									D	
		LIS ON PRI OTI	TED BY "UNDE CODE WIRES E-FIX CAT.NO.	,WP,AL,AS AND J ERWRITERS INC." AND FLEX/24 STI WITH "L" HAS NO CIFIED IN THE SU	" AND "CSA RANDED ( OT PEEP H										_	
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER								В							
С	FINISH:	ELE SPE SUI	]-	A A								С				
<b>→</b>	DIE CODE	INSTALLATION GUIDE DIE CODE = 106 DIE COLOR = Black						R Inspection Hole								
В		USTED 4	NE	BS <sup>3</sup>	<b>(</b>	€		Bevele	d entry			E	/			В
		WIRE CONNECTOR														
																<del></del>
								HUY www.huyaco	A	ELES 76. Hua Panyu [	ncun	Rd. Zh	ongci	ın Tow		
Α				-		WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
	00 14-Dec-	25 Ruby Feng	Sinia Qiu					MATERIAL HIGH-CONDU WROUGHT CO	DA7	558-241		CALE N7		RID ANGLE PE	ROJECTION	
1	REV DATI		CHK	D	DESCRIP		ECN	ELECTRO TIN I	PLATE DWG. NO.	186-cp06	62	nit IN	CH -	<b>⊕</b> £	$\supset$	
		4		I		3	4	2					1			