		4			3	$\downarrow$	2					1			
ı	THE INFORMATION DISCLOSED IN CON	NFIDENCE AND NO	OT TO BE REPRO			CELESTRA CAT.NO	WIRE	SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	R	ID ±0.01	
	DISLOSED EXCEPT	FOR WHICH FUR	NISHED.			WP7558-064	750kcmil	1325/24 = 535 kcmil	7/8	3.96	1.43	1.90	2.26	1.03	
D	NOTE:  MATERIAL:  FINISH:	SPECIFI  2. ALL DA, LISTED ON COE  PRE-FIX OTHERI WITH "P  HIGH CO  SPECIFI	IED.  DB,LA,LB,WP BY "UNDERW DE WIRES ANI CCAT.NO.WIT WISE SPECIFI ".  ONDUCTIVITY DR-TIN PLATE ED PLATE PE	E IN INCHES UN  AL,AS AND J SE  RITERS INC." A  D FLEX/24 STRA  H "L" HAS NOT I  ED IN THE SUF  WROUGHT CO  UNLESS OTHE  R MIL - T -16366  I "SP" FOR SILV		Color coded marking  Bolt Size  B A									
В	INSTALLATIO DIE CODE = DIE COLOR =	106 = Black	NEB		Beveled entry										
Α						CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.  WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									
		<del>                                     </del>	nia Qiu		tandards Spec. Initialed.		MATERIAL HIGH-CONDUCTIVITY PRT. NO. WROUGHT COPPER WP7558-064 NTS THRID ANGLE PROJECTION								
1	REV DATE		CHK	DE:	SCRIPTION	ECN ECN	ELECTRO TIN E	PLATE DWG. NO.	86-cp06	67 U	IN	CH T	ΨŁ		
		4		I	3	4	2					I			