	-	4		1			3	+	2					1			
ı	THE INFORMATION DISCLOSED IN CON	IFIDENCE AND I	NOT TO BE RE					CELESTRA CAT.NO	WIRE		BOLT SIZE	A ±0.06	B MIN	C ±0.04	R	ID ±0.01	
	DISLOSED EXCEPT	FOR WHICH FU	JRNISHED.					LA7558	750kcmil	1325/24 = 535 kcmil	5/8	4.68	1.58	1.94	3.24	1.06	
D 	NOTE: MATERIAL: FINISH:	SPEC 2. ALL D LISTE ON CO PRE-F OTHE WITH HIGH ELECT SPEC	PA,DB,LA,LB D BY "UNDIFODE WIRES FIX CAT.NO. RWISE SPE "P". CONDUCTI TOR-TIN PL IFED PLATE	,WP,AL,A ERWRITE 6 AND FLE WITH "L" ECIFIED IN VITY WRO ATE UNLI E PER MIL	S AND J SE FRS INC." AN EX/24 STRA HAS NOT F N THE SUFF OUGHT COL ESS OTHER L - T -16366.	CAT.NO.S ARE FOR USE BLES. E UNLESS	Color coded marking Bolt Size B B A									D	
В	INSTALLATIO DIE CODE = DIE COLOR =	DN GUIDE 106 = Black	A NE						R	Inspecti	on Hol	e	E				В
	-																_
Α							CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495. TITLE WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
		, ,	Sinia Qiu			<u></u>	pec. Initialed.		MATERIAL HIGH-CONDUC WROUGHT CO FINISH	PPER LA	7558		CALE N	ΓS -	ANGLE P	ROJECTION	
	REV DATE	4	CHK	-	DES	SCRIPTIC 3	N	ECN	electro tin p	PLATE	186-cp06	69	IN	CH 1	₩ <u></u>	7	