		4			3		+	2					1			
ı	THE INFORMATION ON THIS DRAWING IS THE PROERTY OF CELESTRA, IS DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR DISLOSED EXCEPT FOR WHICH FURNISHED.						CELESTRA CAT.NO	WIRE	SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	R	ID ±0.01	
	DISLOSED EXCEPT	FOR WHICH FUI	RNISHED.				LA7538P-260	750kcmil	1325/24 = 535 kcmil	5/8	4.41	0.83	1.91	3.72	1.03	
D	NOTE: MATERIAL: FINISH:	SPECIF 2. ALL DA LISTED ON CO PRE-FI OTHER WITH " HIGH CO ELECT SPECIF	FIED. A,DB,LA,LB,W D BY "UNDER DDE WIRES A IX CAT.NO.W RWISE SPECI P". CONDUCTIVIT FOR-TIN PLAT FED PLATE F	/P,AL,AS AND J S WRITERS INC." ND FLEX/24 STR ITH "L" HAS NOT	ERWISE 66.	.S ARE E SS	Color coded marking Bolt Size O B A									
В	INSTALLATION GUIDE DIE CODE = 106 DIE COLOR = Black NEBS NEBS CELUS LISTED						R Inspection Hole Beveled entry									
Α						CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495. TITLE WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									А	
		, ,	Sinia Qiu	Celestra Standards Spec. Initialed. WROUGHT COPPER LA7538P-260								CALE NTS THRID ANGLE PROJECTION				
1	REV DATE	DWN	CHK	DI	ESCRIPTION 3		ECN	ELECTRO TIN F	PLATE DWG. NO. 1	86-cp06	74 UI	IN	CH 1	ΨL		
		4		l	3		4	2					I			