		4			3		+	2					1								
ı	THE INFORMATION ON THIS DRAWING IS THE PROERTY OF CELESTRA, IS DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR						CELESTRA CAT.NO	WIRE		BOLT SIZE	A ±0.06	B MIN	C ±0.04	R	ID ±0.01						
	DISLOSED EXCEPT	FOR WHICH FURNI	SHED.				LA9158	900 kcmil	1925/24 = 777 kcmil	5/8	5.18	1.58	2.17	3.74	1.19						
									KCIIII												
D	NOTE:	1. ALL DIME SPECIFIE		E IN INCHES U	INLESS OTHE	RWISE	Color coded marking									D					
		LISTED B	Y "UNDERW	,AL,AS AND J S /RITERS INC." / D FLEX/24 STR	AND "CSA" FO	R USE	Bolt Size														
			ISE SPECIF	H "L" HAS NOT IED IN THE SU																	
	MATERIAL:	HIGH CON	NDUCTIVITY		В																
С	FINISH:	SPECIFE	D PLATE PE	UNLESS OTHI R MIL - T -1636 I "SP" FOR SIL										С							
В	INSTALLATIO DIE CODE = 1 DIE COLOR =	115 - Yellow	NEB	S3	€ (€			R	Inspecti d entry	on Hol	<u>e</u>	E				В					
	<u> </u>																				
А								HUY www.huyaco	A	ELES 76. Hua Panyu [ncun	Rd. Zh	nongcu	ın Tow							
				WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									A								
	00 01-Dec-25	, ,	a Qiu		Standards Spe			MATERIAL HIGH-CONDUC WROUGHT CO	PPER LA	9158			TS THR	ID ANGLE PF	ROJECTION						
1	REV DATE	DWN C	HK	DE	ESCRIPTION 3	J	ECN	ELECTRO TIN F	PLATE DWG. NO.	86-cp06	84 ^U	NIT IN	CH 1	Ψ τ							
		4		I	3		4	۷			l		ı								