		4			3		+	2	,		1		1			
1				DERTY OF CELESTRA	A, IS		CELESTRA	WIRE		BOLT	A	В	С	R	ID	
	DISCLOSED IN CO			RODUCED, USED OR	· · · · · · · · · · · · · · · · · · ·	-	CAT.NO	CODE	FLEX 535.3 kcmil	SIZE	±0.06	MIN	±0.04	IX.	±0.01	
							LA5138P-251	-	1325/24 500 kcmi	3/8	4.64	1.16	1.89			
D	NOTE:	SPEC	IFIED.	ARE IN INCHES UN			Color coded marking Bolt Size									D
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".													_		
	MATERIAL:	HIGH	CONDUCTIVI	TY WROUGHT CC	PPER				В							
С	FINISH:	SPEC	IFED PLATE	TE UNLESS OTHE PER MIL - T -16366 ITH "SP" FOR SILV	6.		-		Α	-						С
\rightarrow	INSTALLATION GUIDE DIE CODE = - DIE COLOR = Pink R Inspection Hole										\nearrow		\leftarrow			
В	c (V)	ED	A NI	EBS ³	ROHS.	ϵ	_† [Bevele	d entry			E				В
	WIRE CO	NNECTOR														
															_	_
А								HUY www.huyaco	A	ELES 76. Hua Panyu (ancun	Rd. Zh	ongcu	ın Tow	_	
							WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								Α	
	00 23-Aug-25	Ruby Feng	g Sinia Qiu Celestra Standards Spec. Initialed.					MATERIAL HIGH-CONDU WROUGHT CO	OPPER LA51	38P-251		cale N	rs	ID ANGLE PI	ROJECTION	
1	REV DATE	DWN	CHK	DE	SCRIPTION		ECN	ELECTRO TIN I	PLATE DWG. NO. 1	86-cp07	05	nit IN	CH (+ E	\Box	
		4			3		4	2					1			