| | | 4 | | 1 | | 3 | | + | 2 | | | 1 | | 1 | | | |
|---|--|----------------|----------------------|--|-----------------------------|-------------------------------|--------|--|---------------------|------------------|--------------|------------|-----------|---------------------------|-------------|-------------|---|
| ı | THE INFORMATION OF THE INFORMATI | | | | | | | CELESTRA CAT.NO | WIRE | | BOLT SIZE | A ±0.06 | B MIN | C ±0.04 | R | ID ±0.01 | I |
| | DISLOSED EXCE | PT FOR WHICH I | FURNISHED. | | | | | LA5112P-261 | - CODE | 535.3 kcmil | 1/2 | 4.59 | 1.08 | 1.81 | | ±0.01 | |
| | | | | | | | l | | | 1325/24 500 kcmi | | | | | | | |
| D | NOTE: | | DIMENSION CIFIED. | IS ARE IN IN | ICHES UNLE | SS OTHERWISE | E | Color coded marking Bolt Size | | | | | | | | | D |
| | | LIST | ED BY "UND | B,WP AND J DERWRITER S AND FLEX | S INC." AND | | | | | | | | | | | | |
| | | | ERWISE SP | | | EP HOLE UNLES OF THE CAT.N | | DIE COLOR | | | | | | | | | |
| | MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER B | | | | | | | | | | | | | | | | |
| С | FINISH: | SPE | CIFED PLAT | PLATE UNLE: TE PER MIL - D.WITH "SP" I | - T -16366. | | | - | . , | A | - | | | | | | С |
| | . INSTALLA DIE CODE DIE COLO | | | | | | - 8 | R | Inspecti | on Hol | e | | | | | | |
| В | c. | | ^ N | IEBS | ₅ 3 ₈ | ons (| E | | Bevele | d entry | | | E | | | | В |
| | | ONNECTOR | | | | | | | | | | | | | | | |
| А | | | | | | | | | HUY www.huyaco | A | '6. Hua | ancun | Rd. Zh | RPOF nongcu thou 51 | ın Tow | 'n. | |
| | | | | | | | | WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE | | | | | | | | | |
| | _ | 5 Ruby Feng | | C | | dards Spec. Initia | aled. | | MATERIAL HIGH-CONDU | OPPER LA51 | 12P-261 | | | TS THRI | ID ANGLE PI | ROJECTION | |
| ı | rev date | | CHK | 1 | DESC | RIPTION | | ECN | ELECTRO TIN I | PLATE DWG. NO. 1 | 86-cp07 | 08 0 | nit IN | CH T | Ψ L | | |
| | | 4 | | | | 3 | | 4 | 2 | | | | | 1 | | | |