	-		_						+				ı		_				
	THEI	4 THE INFORMATION ON THIS DRAWING IS THE PROE		PROFRTY	·		3	CELESTRA	2 WIRE SIZE		BOLT	l A	В	1	1	ID	,		
	DISC	LOSED IN CON	IFIDENCE AN	D NOT TO BE					CAT.NO	CODE	FLEX	SIZE	±0.06	MIN	±0.04	R	±0.01		
									DA6556-261	-	646 kcmil 1600/24	5/16	2.82	0.70	1.98	2.16	1.05		
D		NOTE:		. DIMENSION ECIFIED.	IS ARE II	N INCHES UI	NLESS C	THERWISE		Color coded marking Bolt Size									
	_		LIS' ON PRE OTF	TED BY "UNI CODE WIRE E-FIX CAT.NO	DERWRIT S AND F	TERS INC." A LEX/24 STRA L" HAS NOT	AND "CSANDED (DIE CODE DIE COLOR O C C									_	
		MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER									В								
С		FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.							ļ	A									
-		INSTALLATION GUIDE DIE CODE = - DIE COLOR = Black							R Inspection Hole									4	
В	Beveled entry Beveled entry													В					
		LIS	STED CONNECTOR				_												
	1																	_	
										HUY www.huyac	A 7	ELES '6. Hua Panyu I	ancun	Rd. Zh	nongci	un Tov	vn.		
Α										WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									
	00	01-Dec-25	Ruby Feng	Feng Sinia Qiu Celestra Standards Spec. Initialed.						MATERIAL HIGH-CONDUCTIVITY PRT. NO. WROUGHT COPPER DA6556-261 NTS THIRD ANGLE PRO							PROJECTION	1	
1	REV	DATE	DWN	CHK		DE	SCRIP	TION	ECN	FINISH ELECTRO TIN	PLATE DWG. NO. 1	86-cp07	13	nit IN	СН	⊕ {			
			4					3	\uparrow	2					1				