		4	4 3			7	2		11				_		
'	THE INFORMATION	E INFORMATION ON THIS DRAWING IS THE PROERTY OF CELESTRA, IS SCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR			CELESTRA			BOLT	В	С	D	Н	'		
	DISLOSED EXCEP			CERNODOCED, OSED OF			CAT.NO	CODE	FLEX 23 Navy #8 Weld	SIZE	MIN	±0.04	±0.015	±0.01	4
							LA0838F-260	0 8 AWG	37/24 = 14.9 kcmil	3/8	0.83	0.58	0.06	0.18	
									#6 SOL						1
D															D
	NOTE:		DIMENSION CIFIED.	S ARE IN INCHES UI	NLESS OTHERW	VISE									
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE														
	LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.						H BOLT SIZE								
															_
				).WITH "L" HAS NOT ECIFIED IN THE SUF		e state of the control of the contro									
			1 "P".		TIX OF THE OX		_	Ĭ X							
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER							1							
С	FINISH:							<b>⊸</b> B →							
				E PER MIL - T -16366 WITH "SP" FOR SIL\											
								—Ca	lor onded barrel	m a rkir					
									lor coded barrel	markii	igs				
$\rightarrow$	INSTALLATION GUIDE						Wire inspection hole							4	
	DIE CODE = DIE COLOR													7	
									†				_		
В				<b>V</b>				Poveled wir	D o ontra						B
Ь	c(UL)us RoHs,						Beveled wire entry								
		1191	rED.	2002/95/EC											
		WIRE CONN ZMVV/2/7/8.													
									® CELES	TRA	COI	RPO	RATIO	ON	
								HUYA	76. Hua	incun	Rd. Zh	nongci	un Tow	n.	
_					_		<del>                                     </del>	www.huyaco.con	n Panyu [	Dist. G	uangz	hou 5	11495.		
Α							WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE							A	
	00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					Initialed.	MA	ATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	PRT. NO. <b>LA0838F-260</b>	S	CALE N		RID ANGLE PI	ROJECTION	
	REV DATE	DWN	CHK		SCRIPTION		ECN FIN		DWG. NO. 186-cp07	58	NIIT	CH .	<b>(</b>	$\Box$	
		4		I	3		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	2			111	1			'
		•		I	-	_		_		I					