		4		1	,	2	+	0			1		4			
	THE INFORMATION	ON ON THIS DRA	AWING IS THE PRO	OERTY OF CELESTRA		3	V CELESTRA	2 WIRE		BOLT	I A	В	С		ID	1
		ONFIDENCE AN	D NOT TO BE REP	PRODUCED, USED OR			CAT.NO	CODE	FLEX	SIZE	±0.06	MIN	±0.04	R	±0.01	
							LA0814P-251	8 AWG	23 Navy #8 Weld 37/24 = 14.9 kcmil #6 SOL	1/4	1.49	0.62	0.48	0.88	0.18	
D	D NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE Color coded marking SPECIFIED.															D
		LIST	ED BY "UNDER	VP,AL,AS AND J SI RWRITERS INC." A AND FLEX/24 STRA	OR USE	Bolt Size										
		PRE OTH	-FIX CAT.NO.W	VITH "L" HAS NOT CIFIED IN THE SUF	UNLESS	HUYA®										
	MATERIAL	: HIG	H CONDUCTIVI	ITY WROUGHT CC	OPPER		1									
С	FINISH:	SPE	CIFED PLATE	TE UNLESS OTHE PER MIL - T -16366 ITH "SP" FOR SILV	6.		_	/		-						С
-	INSTALLA DIE CODE DIE COLO						- - 8	, R	Inspecti	on Hol	e					\leftarrow
В	С	W us A	NE	BS3 ∰	(€			Bevele	d entry			E				В
		WIRE CONNECTOR														
																_
А								HUY www.huyaco	A	ELES 76. Hua Panyu [incun	Rd. Zh	ongcl	ın Tow	_	
						WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
	00 01-Dec-2	5 Ruby Feng	eng Sinia Qiu Celestra Standards Spec. Initialed.					MATERIAL HIGH-CONDU		14P-251	SC	CALE N7		RID ANGLE PE	ROJECTION	
1	REV DATE	DWN	CHK	DE	SCRIPTIO	N	ECN	FINISH ELECTRO TIN I	81110 110	86-cp00	77 UI	NIT	CH	(E		
		4			3		4	2					1			