		4		3		$\nabla$		2			<u> </u>		1		.
•				PROERTY OF CELESTRA REPRODUCED, USED OR			CELESTRA CAT.NO	WIRE	SIZE FLEX	BOLT SIZE	B MIN	C +0.04	D ±0.015	H +0.01	'
	DISLOSED EXCE					-		CODE	30 Navy 6 Weld						ł
							DA0656F-260	6 AWG	133/.014 61/24 = 24.6 kcmil	5/16	0.70	0.52	0.07	0.22	
D															D
	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.														
		LIST	FED BY "UND	3,WP AND J SERIES ERWRITERS INC." A	ND "CSA" FOR USE		н	I	/-BOLT SIZ	ZE					
		ON CODE WIRES AND FLEX/24 STRANDED CABLES.													
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".													
	MATERIAL	HIG	H CONDUCT	IVITY WROUGHT CO	PPER		Ť								
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.										С				
$\rightarrow$	INSTALLATION GUIDE DIE CODE = 24 DIE COLOR = Blue						Color coded barrel markings								$\Leftrightarrow$
В							D Beveled wire entry								В
		ZMVV/2/7/													
		1													
								ΗυγΑ		incun	Rd. Zh	nongci	un Tow		
•								www.huyaco.con	n Panyu [	Dist. G	uangz	hou 5'	11495.		
A							TITL	WIRE CONNECTORS AND SOLDERING							A
							LUGS FOR CODE AND FLEX CABLE								
	00 23-Aug-2	5 Ruby Feng	Sinia Qiu	Celestra S	tandards Spec. Initialed.			WROUGHT COPPER	PRT. NO. DA0656F-260		CALE N	rs			]
I.	REV DATE	DWN	СНК	DE	SCRIPTION		ECN FINI	ELECTRO TIN PLATE	DWG. NO. 186-cp07	78	NIT IN	СН -	Ф-E		J,
		4			3	4		2				1			
						I									