_					1							
		4		3	\downarrow	2				1		
ı			PROERTY OF CELESTRA, IS		CELEST			BOLT	В	С	D H] '
		NFIDENCE AND NOT TO BE F FOR WHICH FURNISHED.	REPRODUCED, USED OR		CAT.N		FLEX			±0.04 ±		_
					DA1414F	260 14-10 AWG	-	1/4	0.62	0.47	0.047 0.13	4
D												D
	NOTE:		NS ARE IN INCHES UNLE	SS OTHERWISE								
		SPECIFIED.	SPECIFIED. H /BOLT SIZE									
	2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE											
	ON CODE WIRES AND FLEX/24 STRANDED CARLES											
	1	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS										-
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.											
		WITH "P".										
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER											
С	FINISH:		PLATE UNLESS OTHERW	/ISE								l c
	SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											
					. /		noi coded barrer	marking.	·	$\overline{}$		
					45.	Vie color	/ire inspection ho	le	($\backslash \downarrow /$)	
_	INICTALLATIO	INSTALLATION GUIDE										
	DIE CODE = -											
	DIE COLOR :	=					†			4		
							D					
	[∟] Beveled wire entry											
В			,									В
	c (.									
	l "\	2002/95/EC	ĺ									
	WIFE ZAT	RE CONNECTORS										
	1											
							R CELES	TRAC	COR	POR	ATION	1
						HUYA	76. Hua					
	 					www.huyaco.cor						
Α						TITLE WIRE CONNECTORS AND SOLDERING						A
					LUGS FOR CODE AND FLEX CABLE							
						MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION						_
		Ruby Feng Sinia Qiu		dards Spec. Initialed.		WROUGHT COPPER	DA1414F-260		NTS	3 _	h —	`
1	REV DATE	DWN CHK	DESC	RIPTION	ECN	ELECTRO TIN PLATE	DWG. NO. 186-cp00	D8 UNIT	INC) H		J ,
		4		3	\triangle	2				1		
					I							