								1									
			4				3	\bigvee	7	2				1			_
'					PROERTY OF CE REPRODUCED, L				CELESTRA			BOLT	В	С	D	Н	l '
			FOR WHICH		REPRODUCED, (JSED OR			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.01	
							-		DA043F-26	1 4 AWG	40-50 Navy 133/.0177 49/.029 91/24 = 36.7 kcmil	3/8	0.83	0.58	0.08	0.28	
D																	l _D
_	NO	OTE:		DIMENSION CIFIED.	IS ARE IN INC	HES UNLESS	OTHERWISE										
		 ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. 							H BOLT SIZE								
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
	M	ATERIAL:	HIG	H CONDUCT	TIVITY WROUG	HT COPPER			1								
С	C FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.								} -						С		
→	INSTALLATION GUIDE DIE CODE = 29 DIE COLOR = Gray								Color coded barrel markings Wire inspection hole								
В	CUL US ROHS									Beveled win	D re entry						В
		WIR ZMR	E CONNECTORS V/2/7/8 E513913														
	<u> </u>		I														
									HUYA® Www.huyaco.com CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.								
Α									TITLE WIRE CONNECTORS AND SOLDERING								Α
										LUGS FOR CODE AND FLEX CABLE							
	00	02-Dec-25	Ruby Feng	ıby Feng Sinia Qiu Celestra Standards Spec. Initialed.					MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE WROUGHT COPPER DA043F-261 NT:						RID ANGLE PR	PROJECTION	
1	REV	DATE	DWN	CHK		DESCRI	PTION		ECN FI	ELECTRO TIN PLATE	DWG. NO. 186-cp08	37 Ut	NIT IN	CH -	(E	\exists	
			4				3	4	7	2				1			
								- 1									