									1									
			4					3	\downarrow	7	2				1			
1		E INFORMATION ON THIS DRAWING IS THE PROERTY OF CELESTRA, IS SCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR			CELESTRA	•	E SIZE	BOLT	В	С	D	Н	'					
			FOR WHICH		REPRODUC	ED, USED OR			-	CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.01	1
										LA0414FP-26	61 4 AWG	40-50 Navy 133/.0177 49/.029 91/24 = 36.7 kcmil	1/4	0.64	0.55	0.09	0.28	
D	NO.	OTE:	1 All	DIMENSION	IS ARF IN	INCHES UNU	ESS OT	HERWISE										D
	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE																	
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.								H BOLT SIZE								
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".									C C								
	M	ATERIAL:	HIGI	H CONDUCT	IVITY WR	OUGHT COP	PER											
С	FII	NISH:	ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С				
→	DI	INSTALLATION GUIDE DIE CODE = 29 DIE COLOR = Gray								Color coded barrel markings Wire inspection hole								\leftarrow
В			C U		Rol-	HS.				Beveled wire entry								В
																		_
										 		A . OF ! E	TDA	00'		DATI	ON!	1
											HUY/ www.huyaco.co		ancun	Rd. Zh	nongc	un Tow	'n.	
Α	\vdash									TITLE WIRE CONNECTORS AND SOLDERING								Α
	$\mid \mid \mid$								LUGS FOR CODE AND FLEX CABLE									
	00	23-Aug-25	Ruby Feng	Sinia Qiu		Celestra Star	ndards S	Spec. Initialed.		М.	MATERIAL HIGH-CONDUCTIVIT WROUGHT COPPER		S	CALE N	TS TH	RID ANGLE P	ROJECTION	1
	REV	DATE	DWN	СНК		DESC	CRIPTI	ION		ECN FII	INISH ELECTRO TIN PLATE	DWG. NO. 186-cp08	54 ^U	nit In	ICH	+ +] ,
			4				3	}	4	7	2				1			