		4		3	$\Box$		2				1			
ı			HE PROERTY OF CELESTRA, BE REPRODUCED, USED OR	S		CELESTRA	WIRE		BOLT	В	С	D	Н	'
		T FOR WHICH FURNISHE			_	CAT.NO	CODE	FLEX 60 Navy #4 Weld	SIZE	MIN	±0.04	±0.015	±0.01	
						DA0214F	2 AWG	125/24 = 50.5 kcmil	1/4	0.65	0.59	0.11	0.30	
D														D
	NOTE:	<ol> <li>ALL DIMENS</li> <li>SPECIFIED.</li> </ol>	ONS ARE IN INCHES UNL	ESS OTHERWISE										
	LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE													
		ON CODE WI	RES AND FLEX/24 STRAN	IDED CABLES.		<u>*</u>								
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS													
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".													
	MATERIAL:	HIGH CONDU	ICTIVITY WROUGHT COP	PER										
_	B													С
C	C FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.													
		SUFFIX CAT.	NO.WITT OF FOR SIEVE	N.		λ	Co	lor coded barrel	markin	ıas				
						ŝ				J				
_	INIOTALLAT	INSTALLATION GUIDE				Wire inspection hole							_	
	DIE CODE =	DIE CODE = 33												$\leftarrow$
	DIE COLOR = Brown													
								Ţ						
							- Royalad wir	D co optrv						
В			/		Beveled wire entry								В	
	l c	(UL)US ROL	/ IS,											
		LISTED	/EC											
	y,	MRE CONNECTORS ZMVV/2/7/8,E513B13												
	1													
							AVIIL	® CELES						
۸					HUYA® CELESTRA CORPORA 76. Huancun Rd. Zhongcun							n.		
					www.huyaco.com Panyu Dist. Guangzhou								_	
Α						WIRE CONNECTORS AND SOLDERING								Α
						LUGS FOR CODE AND FLEX CABLE								
	00 02-Dec-25	Ruby Feng Sinia Q	Feng Sinia Qiu Celestra Standards Spec. Initialed.			MATI	ERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	PRT. NO. <b>DA0214F</b>	SC	CALE N		RID ANGLE PE	ROJECTION	
	REV DATE	DWN CHK		CRIPTION		ECN FINIS		DWG. NO. 186-cp08	56 UI	VIIT	CH .	<b>⊕</b> €	$\exists$	_
		4	1	3	$\Delta$		2	,			1	•		
		-	I	-	7		_		I					