		4			3	7	7	2				1			
l		THE INFORMATION ON THIS DRAWING IS THE PROERTY OF CELESTRA, IS DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR						WIRE		BOLT	В	С	D	Н	1 '
		CEPT FOR WHICH		EPRODUCED, USED OR			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.015	±0.01	ł
							DA0256F-252	2 AWG	60 Navy #4 Weld 125/24 = 50.5 kcmil	5/16	0.76	0.66	0.10	0.31	
								•							
D															D
	NOTE:	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.													
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE  H  BOLT SIZE														
	LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.														
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS													l —
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".  MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER									Ĺ					
С	FINISH:		ELECTOR-TIN PLATE UNLESS OTHERWISE									С			
			CIFED PLATI FIX CAT.NO.												
							$\rightarrow$	Co	lor coded barrel	markin	ıgs		_		
	INSTALI	ATION GUIDE			Wire inspection hole										
	DIE COI	E = 33													
	DIE COI	OR = Brown					<u> †                                   </u>					L			
									l D			·			
	Beveled wire entry														
В	B Develed wire entry										В				
				2002/95/EC											
		LIS	TED NECTORS												
		ZMVV/2/7/													
_															<b> </b> —
			<u> </u>				1 1								
								HUYA	®   CELES						
								www.huyaco.con						n.	
Α								<u> </u>	,						Α
A							WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE							^	
	00 23-Au	g-25 Ruby Feng	by Feng Sinia Qiu Celestra Standards Spec. Initialed.			l.	MA	ATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	PRT. NO. <b>DA0256F-252</b>	SC	CALE N		RID ANGLE PI	ROJECTION	
	REV DA		СНК	DESC	RIPTION		ECN FIN		DWG. NO. 186-cp08	74 UI	VIIT	CH	<b>(</b> (	$\exists$	
		4	1	1	3			2	· .			1			'
L				I			Γ			ı					