	-		л		I		3	<	7	2		1		1			
							3	N	/		0175		_		_		1
	DISCL	OSED IN COM	FIDENCE AND	D NOT TO BE	PROERTY OF CEI REPRODUCED, U				CELESTRA CAT.NO	CODE	SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	H +0.01	
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.							60 Navy #4 Weld						1
									LA0214F-260	2 AWG	125/24 = 50.5 kcmil	1/4	0.64	0.60	0.11	0.30	
																_	I
D																	D
D	N	OTE:		DIMENSION CIFIED.	NS ARE IN INCH	IES UNLESS	OTHERWISE										
2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.									H BOLT SIZE								
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
	M	IATERIAL:	HIGI	H CONDUC	TIVITY WROUG	HT COPPER					-						
С	F	INISH:	SPE	CIFED PLA	PLATE UNLESS TE PER MIL - T).WITH "SP" FO	-16366.	E				I						С
\rightarrow	INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown										ngs				\downarrow		
В	Beveled wire entry														В		
	1																
										HUYA		ncun	Rd. Zh	nongci	un Tow		
А									TITLE WIRE CONNECTORS AND SOLDERING								A
									LUGS FOR CODE AND FLEX CABLE								
	00	23-Aua-25	Ruby Feng	Sinia Qiu	Cel	estra Standar	ds Spec. Initialed.		MA	TERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	PRT. NO. LA0214F-260		CALE	ТНЕ	RID ANGLE PR	ROJECTION	
	REV	DATE	DWN	СНК		DESCRI			ECN FIN		DWG. NO. 186-cp08	89 0	NIIT	CH -	ŒE	\square	
	·	1	4	1			3	4		2				1			