	-		4		1		3	3	4	7	2		1		1				
l	DISCL	LOSED IN CON	VEIDENCE AND	O NOT TO BE	PROERTY C REPRODUCE	F CELESTRA, IS ED, USED OR		<u>, </u>	Ĭ	CELESTR.	A WIRE	SIZE	BOLT SIZE	B MIN	C ±0.04	D ±0.015	H ±0.01] '	
5		DSED EXCEPT	FOR WHICH	FURNISHED.						DA0112F		75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223	1/2	1.25	0.76	0.11	0.36	D	
D		NOTE:		DIMENSION CIFIED.	IS ARE IN	INCHES UNLES	SS OTHE	RWISE											
_			LIST	ED BY "UNI	DERWRITE	J SERIES OF (RS INC." AND EX/24 STRANDI	"CSA" FO	OR USE		н /—BOLT SIZE									
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								e shift C									
	N	MATERIAL:	HIGI	H CONDUCT	ΓΙVITY WR	OUGHT COPPE	ĒR												
C	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С						
	<u></u>	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green								Color coded barrel markings Wire inspection hole									
В		CUL US ROHS									Beveled wi	D re entry			<u> </u>			В	
_			WIRE CONN ZMVV/2/7/8															_	
											HUYA www.huyaco.com	_	incun	Rd. Zh	nongci	un Tow	n.		
А										1	WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE							А	
	00	23-Aug-25	Ruby Feng	by Feng Sinia Qiu Celestra Standards Spec. Initialed.						MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE NT. DA0112F						RID ANGLE P	LE PROJECTION		
ı	REV	DATE	DWN	CHK		DESC	RIPTION	V		ECN F	ELECTRO TIN PLATE	DWG. NO. 186-cp09	04	init In	СН	(],	
	_		4				3		4	7	2				1				