									I				·					
		4 3		3	2				1					-				
·	DISCLOSE	HE INFORMATION ON THIS DRAWING IS THE PROERTY OF CELESTRA, IS ISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR				CELE		WIRE SIZE  CODE FLEX		BOLT SIZE	B MIN	C +0.04	D ±0.015	H ±0.01				
_	DISLOSED	EXCEPT	FOR WHICH	FURNISHED.					DA0114		1 AWG	75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223	1/4	0.63	0.70	0.11	0.36	
ט	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.																	D
_			LIST ON ( PRE	ED BY "UNE CODE WIRE -FIX CAT.NO	DERWRITI S AND FL D.WITH "L	) J SERIES OF ERS INC." AND EX/24 STRAND " HAS NOT PEI N THE SUFFIX	"CSA" FO DED CABL EP HOLE	OR USE LES. UNLESS		H BOLT SIZE								
			WITI	H "P".							Huya (	Ç						
	MATE	ERIAL:	HIGH	H CONDUCT	TIVITY WR	OUGHT COPP	ER			<b>A</b>		<u> </u>						
С	FINIS	ISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С					
$\rightarrow$	DIE C	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green							45°	Color coded barrel markings  Wire inspection hole								
В		CUL US  LISTED  WIRE CONNECTORS								D Beveled wire entry								
			WIRE CONN ZMVV/2/7/8															_
											HUYA ww.huyaco.com		incun	Rd. Zh	nongci	un Tow	'n.	
Α										WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								A
	00 23-	23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.				ec. Initialed.		MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PRO. WROUGHT COPPER DA0114F-250 NTS							ROJECTION	1		
	-	DATE	DWN	СНК		DESC	RIPTION	N	ECN	FINISH		DWG. NO. 186-cp09	05	NIIT	CH	<b>(</b>		
		ı	4				3		4		2				1			