			1		ı		3		+		2		1		1			
	THE IN	NFORMATION	I ON THIS DRA	WING IS THE	PROERTY C	OF CELESTRA, IS	\top		CELES		WIRE		BOLT	В	С	D	Н	l '
			FOR WHICH		REPRODUC	ED, USED OR			CAT.N	10	CODE	FLEX 75 Navy #2 Weld	SIZE	MIN	±0.04	±0.015	±0.01	ł
									DA0156F	-250	1 AWG	150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223	5/16	0.76	0.70	0.11	0.36	
D	N	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.													D			
			LIST	ED BY "UNI	DERWRITE	J SERIES OF (ERS INC." AND EX/24 STRAND	"CSA" FOR L	JSE		ӊBOLT SIZE								
			OTH			' HAS NOT PEE N THE SUFFIX			C C									
	М	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.												С					
\rightarrow	D	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green							Color coded barrel markings Wire inspection hole									4
В		CUL US LISTED WIRE CONNECTORS								D Beveled wire entry								
_			ZMVV/2/7/8															_
										_	HUYA ww.huyaco.cor	76. Hua	STRA CORPORATION uancun Rd. Zhongcun Town. u Dist. Guangzhou 511495.					
Α										WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								А
	00	23-Aug-25	Ruby Feng	y Feng Sinia Qiu Celestra Standards Spec. Initialed.						MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID AI WROUGHT COPPER DA0156F-250 NTS							ROJECTION	
ı	REV	DATE	DWN	СНК		DESC	RIPTION		ECN	FINISH		DWG. NO. 186-cp09	06	init In	CH .	(] ,
			4				3		\triangle		2				1			