								ı									
			4				3		7	2				1	l		
'			I ON THIS DRA NFIDENCE AND			OF CELESTRA, IS			CELESTR			BOLT	В	С	D	Н	.
			FOR WHICH		KEFKODOC	LD, OSLD OK			CAT.NO DA0156F-2		FLEX 225/24 #1 Weld	SIZE 5/16	MIN 0.70	±0.04		±0.01 0.39	I
									DAU150F-2	201 TAVVG	225/24 # i vveid	5/16	0.70	0.75	0.12	0.39	
D																	D
	N	IOTE:			IS ARE IN	INCHES UNLES	S OTHERWISE			Н	/-BOLT S	ZE					
			SPECIFIED.														
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE 							2								
	ON CODE WIRES AND FLEX/24 STRANDED CABLES.								C								
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.																
		WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER								_							
	N	IATERIAL:	HIGH	H CONDUCT	FIVITY WR	OUGHT COPPE	R										
С	F	INISH:		ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.						Color coded barrel markings							С
						P" FOR SILVER.			% /								
									45° +3°	Vie co.	/ire inspection h	ole			_		
									/		↓						
\rightarrow	IN	NSTALLATIO	ON GUIDE						•								4
		IE CODE =									Ţ						7
		TE OOLOIV.	- Orcon							Davided wi	D ro ontmi						
										[∟] Beveled wi	re entry						
_					_	/											l _
В			_(Ս) II9	Pol	1 0											В
			0		2002/9	5/EC											
			LIST WIRE CONN														
			ZMVV/2/7/8														
																	
		I	I														
										HUYA	® CELE						
	_								76. Huancun Rd. Zhongcun Tow www.huyaco.com Panyu Dist. Guangzhou 511495.							١.	
А									-								۸
A										WIRE CONNECTORS AND SOLDERING							Α
										LUGS FOR CODE AND FLEX CABLE							
	00	00 04-May-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.						ed.	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PRI WROUGHT COPPER DA0156F-261 NTS							JECTION	
	REV		DWN	СНК			PIPTION		ECN	FINISH ELECTRO TIN PLATE	DWG. NO. 186-cp0		NIIT	ICH	$\oplus \in$	\exists	
		ı	4				3	Δ	\	2				1	<u> </u>		
			-		I		-	7				I					