	,																		
			4					3		<u> </u>	2				1	<u> </u>		•	
'	THE INI	IE INFORMATION ON THIS DRAWING IS THE PROERTY OF CELESTRA, IS SCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR					CELESTRA CAT.NO	• •	WIRE SIZE		B MIN	C +0.04	D ±0.015	H ±0.01					
			FOR WHICH							LA0110F	3322	FLEX 75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223	#10	0.65	0.68	0.11	0.36		
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.													D					
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". 									H BOLT SIZE								
	M.A	ATERIAL:	HIGI	H CONDUCT	IVITY WR	OUGHT COPF	PER												
С	FII	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С						
→	DII	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green								Color coded barrel markings Wire inspection hole									
В		CULUS ROHS								D Beveled wire entry									
			WIRE CONI ZMVV/2/7/8															_	
											HUY/ www.huyaco.co		ncun	Rd. Zh	nongci	un Tow	n.		
Α									WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								A		
	00 2	23-Aug-25	Ruby Feng	Sinia Qiu		Celestra Stan	ndards Sp	ec. Initialed.		N	MATERIAL HIGH-CONDUCTIVIT WROUGHT COPPER		S	cale N		RID ANGLE P	ROJECTION		
	REV	DATE	DWN	CHK		DESC	CRIPTIO	N		ECN F	ELECTRO TIN PLATE	DWG NO	28	NIIT	СН	(1)			
			4				3		4	`	2				1				