			1		ı		3		+		2		1		1			
	THE IN	NFORMATION	I ON THIS DRA	WING IS THE	PROERTY C	OF CELESTRA, IS	$\overline{}$			ELESTRA	WIRE	SIZE	BOLT	В	С	D	Н	l '
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.	REPRODUC	ED, USED OR			C	CAT.NO	CODE	FLEX 75 Navy #2 Weld	SIZE	MIN	±0.04	±0.015	±0.01	
									LA0	0156F-260	1 AWG	150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223	5/16	0.70	0.68	0.10	0.36	
D	N	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.														D		
			LIST	ED BY "UNI	DERWRITE	J SERIES OF ERS INC." AND EX/24 STRAND	"CSA" FOR U	JSE		н /—BOLT SIZE								
			OTH			' HAS NOT PEE N THE SUFFIX			C									
	М	IATERIAL:	HIGI	H CONDUCT	TIVITY WR	OUGHT COPPI	ĒR											
С	FI	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С					
\rightarrow	D	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green							Color coded barrel markings Wire inspection hole									\leftarrow
В		CULUS ROHS LISTED WIRE CONNECTORS								'	Beveled wi	D re entry				J		В
			ZMVV/2/7/8															_
											HUYA www.huyaco.com	_	ncun	Rd. Zh	nongci	ın Tow	n.	
Α										TITL	WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE							
	00	23-Aug-25	Ruby Feng	y Feng Sinia Qiu Celestra Standards Spec. Initialed.						MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE TWO WROUGHT COPPER LA0156F-260 NTS							ROJECTION	
1	REV	DATE	DWN	СНК		DESC	RIPTION		E	CN FINI		DWG. NO. 186-cp09	33	INIIT	CH	(] ,
			4				3		\triangle		2				1			