			Л		1		,	3	4	7	2		I		1			
	THE IN	NFORMATION	ON THIS DRA	WING IS THE	PROERTY C	OF CELESTRA, IS	一 <u>`</u>	<u> </u>		CELESTRA	WIRE	SIZE	BOLT	В	С	D	Н	1 '
	DISCL	SED EXCEPT	FOR WHICH	FURNISHED.	REPRODUC	ED, USED OR				CAT.NO	CODE	FLEX 75 Navy #2 Weld	SIZE	MIN	±0.04	±0.015	±0.01	1
										LA0112FP-26	1 AWG	150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223	1/2	1.08	0.83	0.09	0.36	
D	N	NOTE:  1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.													D			
			LIST	ED BY "UNI	DERWRITE	) J SERIES OF ERS INC." AND EX/24 STRAND	"CSA" F	OR USE		н /—BOLT SIZE								
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".								C C								
	М	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																
С	FI	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С					
$\rightarrow$	D	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green								Color coded barrel markings  Wire inspection hole								
В		CUL US ROHS								D Beveled wire entry								
			WIRE CONN ZMVV/2/7/8	IECTORS E513913														_
					_				HUYA® Www.huyaco.com  CELESTRA COR 76. Huancun Rd. Zhe Panyu Dist. Guangzh						gcun Town.			
Α										TI	WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE							
	00	23-Aug-25	Ruby Feng	uby Feng Sinia Qiu Celestra Standards Spec. Initialed.						M	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE LA0112FP-260 NT							1
ı	REV	DATE	DWN	СНК		DESC	RIPTIO	N		ECN FII	NISH ELECTRO TIN PLATE	DWG. NO. 186-cp09	37	nit In	ICH .	<b>(</b>		] ,
			4				3		4		2				1			