		4			3 7	∇		2				1			
				ERTY OF CELESTRA, IS RODUCED, USED OR		CELEST		WIRE		BOLT	B C	D	H		
		CEPT FOR WHICH				CAT.N		CODE	FLEX 100 Navy #1 Weld	SIZE	MIN ±0.0	4 ±0.015	±0.01		
						DA1038F	-250	1/0 AWG	255/24 = 90.8 kcmil	3/8	0.83 0.76	0.12	0.39		
									133/.0254						
D														D	
	NOTE:		DIMENSIONS A	RE IN INCHES UNLESS	OTHERWISE										
				P AND J SERIES OF CA											
			WRITERS INC." AND "C ND FLEX/24 STRANDED		H BOLT SIZE										
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS													—	
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.														
		WIT	Ή "P".						¥						
	MATERI	AL: HIG	H CONDUCTIVIT	Y WROUGHT COPPER			I								
С	FINISH:			E UNLESS OTHERWISE ER MIL - T -16366.	Ē			⊢ ⊸ B						С	
				TH "SP" FOR SILVER.											
							2	Cc	lor coded barrel	marking	19				
					~				manning						
\rightarrow		INSTALLATION GUIDE						Wire inspection hole							
	DIE COI DIE COI	0E = 42 .OR = Pink				4	1		Ţ					7	
									1			_			
D	B Beveled wire entry						D					В			
D															
				2002/95/EC											
		LIS WIRE CON ZMVV/2/7/													
	1													—	
										TDA	CORPC		אר		
								ΙυγΑ			d. Zhongo				
						_	. – –	w.huyaco.cor			angzhou				
А					TITLE WIRE CONNECTORS AND SOLDERING					A					
						_	LUGS FOR CODE AND FLEX CABLE								
	├ ─- ├ ─-											HRID ANGLE PF	OJECTION		
		-25 Ruby Feng			ds Spec. Initialed.		FINISH	WROUGHT COPPER	DA1038F-250		NTS	€	\neg		
1	REV DA		СНК	DESCRI		ECN		ELECTRO TIN PLATE	186-cp09	50	INCH			1	
	4 3							2				1			
						1									