															$\overline{}$
		4			3	3 🔻		2		11				_	
'	THE INFORMATION ON THE DISCLOSED IN CONFIDEN		RAWING IS THE ND NOT TO BE I	PROERTY OF CELESTRA, IS REPRODUCED, USED OR			CELESTRA			BOLT		C	D	H	'
		XCEPT FOR WHIC					CAT.NO	CODE	FLEX 100 Navy #1 Weld	SIZE	MIN	±0.04	±0.015	±0.01	ł
							DA1014F-260	1/0 AWG	255/24 = 90.8 kcmil	1/4	0.64	0.75	0.12	0.39	
						L	,		133/.0254						ł
D															D
	NOTE:		L DIMENSION PECIFIED.	IS ARE IN INCHES UNLE											
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE														
	LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.						H BOLT SIZE								
															 —
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.						C								
			ITH "P".				T T T T T T T T T T T T T T T T T T T								
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER														
С	FINISH			LATE UNLESS OTHERV	VISE		B							l _c	
Ū				TE PER MIL - T -16366. D.WITH "SP" FOR SILVER											
							\wedge	Co	lor coded barrel	markin	ıgs	\leftarrow			
	INSTA	INSTALLATION GUIDE						Wire inspection hole							
	DIE CO	DE = 42													
	DIE COLOR = Pink														
									†			4	_		
-				./					D						
В	B C (UL) US ROHS						[∟] Beveled wir	Beveled wire entry						В	
		~ ~		2002/95/EC											
			ONNECTORS 07/8.E513913												
		EMI V	rra.Lataria												
	1														
									® CELES	TDA	COI		D ATI)NI	1
								HUYA	R 76. Hua					_	
								www.huyaco.con							
Α								WIRE CONNECTORS AND SOLDERING							Α
							LUGS FOR CODE AND FLEX CABLE								
							ΓΔΝΑ		PRT. NO.		CALE		RID ANGLE PI	ROJECTION	1
	-							WROUGHT COPPER	DA1014F-260		NIT N		(h) -[
1	REV D	ATE DWN	CHK	DESC	CRIPTION	A	ECN FINI	ELECTRO TIN PLATE	186-cp09	52 "	IN	CH	\(\psi\)		1 1
		4			3	4	7	2				1			
						1									