						1									
		4 3		\bigvee	2			1					_		
1	THE INFORMA	HE INFORMATION ON THIS DRAWING IS THE PROERTY OF CELESTRA SCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR		PROERTY OF CELESTRA, IS			CELESTRA	WIRE		BOLT	В	С	D	Н	'
		CEPT FOR WHICH					CAT.NO	CODE	FLEX 100 Navy #1 Weld	SIZE	MIN	±0.04	±0.015	±0.01	
							DA1038F-260	1/0 AWG	255/24 = 90.8 kcmil	3/8	0.83	0.75	0.12	0.39	
									133/.0254						
D															D
	NOTE:		DIMENSIONS CIFIED.	S ARE IN INCHES UNLE											
				WD AND LEEDIES OF	CATNOSADE										
	 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE 						H / BOLT SIZE								
	ON CODE WIRES AND FLEX/24 STRANDED CABLES.						DOLI GIZE								
				.WITH "L" HAS NOT PEI											
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".														
	MATERIA	ΛΙ· HIG	HIGH CONDUCTIVITY WROUGHT COPPER												
_	FINISH:														
С	SPECIFED PLATE PER MIL - T -16366.														С
		SUF	FIX CAT.NO.	WITH "SP" FOR SILVER											
							\rightarrow	Co	lor coded barrel	markin	gs		_		
							<u>ကို</u>	day							
\rightarrow	INSTALLATION GUIDE DIE CODE = 42						Wire inspection hole							\leftarrow	
		OR = Pink													
							<u> † </u>					L			
									D D						
В	в 🗸 🗸							Beveled wire entry							В
	CUL) US ROHS														
		LIS.	TED												
		WIRE CON ZMVV/2/7/8													
															l
									® CELES	TRA	COF	RPO	RATIO	NC	
								AYUH						n.	
								www.huyaco.con	n Panyu [)ıst. G	uangz	hou 5	11495.		١.
Α							TITLE WIRE CONNECTORS AND SOLDERING							A	
							LUGS FOR CODE AND FLEX CABLE								
	00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					.	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION WROUGHT COPPER DA1038F-260 NTS								
	REV DAT		CHK		RIPTION		ECN FINIS	WROUGHT COPPER ELECTRO TIN PLATE	DWG. NO. 186-cp09	3 UI	NIT IN		⊕ €	\exists	
		4		<u> </u>	3			2	100 0009	~ 	IIV	<u> П</u>	т		1
		7		I	J	4		~		I		'			