	,														
		4 3		3	\bigvee	2					1			_	
'	THE INFORMAT	THE INFORMATION ON THIS DRAWINDISCLOSED IN CONFIDENCE AND NO		PROERTY OF CELESTRA, IS REPRODUCED, USED OR			CELESTRA			BOLT	В	С	D	Н	'
		EPT FOR WHICH		LET NOBOCES, COED ON			CAT.NO	CODE	FLEX 100 Navy #1 Weld	SIZE	MIN	±0.04	±0.015	±0.01	
						DA	A1012F-260	1/0 AWG	255/24 = 90.8 kcmil	1/2	1.08	0.75	0.12	0.39	
									133/.0254						
D															D
	NOTE:		DIMENSION CIFIED.	S ARE IN INCHES UNLI											
				NID AND LEEDIES OF											
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.						H / BOLT SIZE								
															l —
				.WITH "L" HAS NOT PE											
		OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".													
	MATERIA			IVITY WROUGHT COP	PER										1
_	FINISH:							В	-						
С	SPECIFED PLATE PER MIL - T -16366.						· ·								С
		SUF	FIX CAT.NO.	WITH "SP" FOR SILVER	₹.										
							\rightarrow	Co	lor coded barrel	markin	ngs		_		
							<u>ကို</u> /	No.							
\rightarrow	INSTALLATION GUIDE DIE CODE = 42						Wire inspection hole							\leftarrow	
	DIE COLOR = Pink														
									l D			·			
В	Beveled wire entry												В		
	C(UL)US ROHS							20.0.04 0 1							
		LIS.	TED												
		WIRE CON ZMVV/2/7/													
								11137 A	® CELES	TRA	COI	RPO	RATIO	NC	
								AYUH	76. Hua	ncun	Rd. Zh	ongci	ın Tow	_	
								/ww.huyaco.con	n Panyu [Dist. G	uangz	hou 5	11495.		1
Α								WIRE CONNECTORS AND SOLDERING							Α
							LUGS FOR CODE AND FLEX CABLE								
	00 23-Aug-	00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					MATE	ERIAL HIGH-CONDUCTIVITY	PRT. NO.		CALE	ТНЕ	RID ANGLE PF	ROJECTION	1
	REV DATE		CHK		CRIPTION		ECN FINIS	WROUGHT COPPER	DA1012F-260 DWG. NO. 186-cp099	- UI	TIN		⊕ €	7	
	INLV DAIL	4	CLIK	l DESC	3		LOIN	ELECTRO TIN PLATE	186-cp099	04 	IN	CH 1	4	7	¹
		4		I	3	4		۷		I		ı			