						I									
		4 3		3		7	2			1				_	
1	THE INFORMATION ON THIS DRAWING IS TO DISCLOSED IN CONFIDENCE AND NOT TO		WING IS THE F	PROERTY OF CELESTRA,	S		CELESTRA	WIRE		BOLT	В	С	D	Н	l '
	DISLOSED EXCEP					-	CAT.NO	CODE	FLEX 100 Navy #1 Weld	SIZE	MIN	±0.04	±0.015	±0.01	ł
							DA1014F-252	1/0 AWG	255/24 = 90.8 kcmil	1/4	0.70	0.76	0.12	0.39	
						l			133/.0254						ļ
D															D
	NOTE:		DIMENSIONS CIFIED.	S ARE IN INCHES UNI											
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE														
	LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.						H BOLT SIZE								
															l—
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS														
		OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".													
	MATERIAL:	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER													
С	FINISH:		ELECTOR-TIN PLATE UNLESS OTHERWISE					⊸ B →							l _c
Ŭ				E PER MIL - T -16366. WITH "SP" FOR SILVE	R.										~
							\nearrow	Co	lor coded barrel	markin	igs				
_	INSTALLATI	ON CLUDE					45° ±3°	Colar	ire inspection ho	ام					
	DIE CODE =	: 42													
	DIE COLOR = Pink														
							<u>, </u>		<u> </u>						
				,					D						
В	Beveled wire entry										В				
				ROHS 2002/95/EC											
		LIST	ED												
		ZMVV/2/7/8.1													
															
		1 '					1 1								
								HUYA	® CELES					_	
														n.	
۸								www.huyaco.con	,						1
Α								WIRE CONNECTORS AND SOLDERING							A
							LUGS FOR CODE AND FLEX CABLE								
	00 23-Aug-25	00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.				d.	MATERIAL HIGH-CONDUCTIVITY PRT. NO. WROUGHT COPPER DA1014F-252 NTS							ROJECTION	1
	REV DATE	DWN	СНК	DES	CRIPTION		ECN FINI		DWG. NO. 186-cp096	10 06	IN		(E	\rightarrow	.
		4			3	Δ		2		i		1			'
				ı		Т				'					