									I										
		4			3		$\sqrt{}$	2				11				_			
ı	THE INFO	THE INFORMATION ON THIS DRAWING IS THE PROE DISCLOSED IN CONFIDENCE AND NOT TO BE REPRO		PROERTY OF	RTY OF CELESTRA, IS DDUCED, USED OR			CELEST				BOLT	В	C	D	H	Ì '		
			FOR WHICH		TEL ROBOGED				CAT.N	0	CODE	FLEX 125 Navy 1/0 Weld	SIZE	MIN	±0.04	±0.015	±0.01	1	
									DA2014	4F	2/0 AWG	275/24 = 111 kcmil	1/4	0.65	0.83	0.13	0.44		
												133/.0282						4	
D																		D	
	ГОИ	ΓE:			IS ARE IN IN	ICHES UNLES	S OTHERWIS	SE											
		SPECIFIED.																	
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. 							H BOLT SIZE										
																		l	
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS								C C										
		OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																	
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																		
											⊸B								
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.							, b ,									С		
			SUF	FIX CAT.NO	.WITH "SP" I	FOR SILVER.													
										λ	Cc	olor coded barrel	markir	nas	1				
\rightarrow		TALLATIC	ON GUIDE						45° ±3°		(Die Con.)	/ire inspection ho	le			1		\leftarrow	
		COLOR =							/	\		↓							
									•										
												Ţ							
В									Beveled wire entry									В	
Ь																			
			1101	CD	2002/95/EC														
			WIRE CONN ZMVV/2/7/8																
	1																	_	
												® CELES	TDA	<u></u>		DATI)N	1	
										Н	UYA	76. Hua							
									-		w.huyaco.cor								
Α								WIRE CONNECTORS AND SOLDERING								Α			
									LUGS FOR CODE AND FLEX CABLE										
											HIGH-CONDUCTIVITY			CALE			SO IECTION	-	
	-					tialed.			WROUGHT COPPER	DA2014F		N ⁻	NTS THRID ANGLE PROJECTION						
1	REV	DATE	DWN	CHK		DESCF	RIPTION		ECN	FINISH	ELECTRO TIN PLATE	DWG. NO. 186-cp09	93 0	nit IN	СН	Ψτ] ,	
	,		4				3	۷	\uparrow		2				1				
									I										