									7								
		HE INFORMATION ON THIS DRAWING IS THE PROERTY OF CELESTRA, I			3		/	2 STRA WIRE SIZE			1				,		
	DISCL	OSED IN CON	NFIDENCE AND	NOT TO BE I					CELESTR. CAT.NO	• •	SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	D ±0.015	H ±0.01	
	DISLO	ISED EXCEPT	FOR WHICH I	-URNISHED.			J		DA2014F		125 Navy 1/0 Weld 275/24 = 111 kcmil 133/.0282	1/4	0.65	0.83	0.13	0.44	
D	N	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.														D	
_	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. DREE FLY CAT NO WITH "I " LIAS NOT REED HOLE LINESS															_	
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
		MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER □ B □															
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.												С			
\rightarrow	D	INSTALLATION GUIDE DIE CODE = 45 DIE COLOR = Black								Wire inspection hole							
В	Beveled wire entry LISTED WIRE CONNECTORS														В		
			ZMVV/2778														
										HUYA www.huyaco.com	_	ncun	Rd. Zh	nongci	un Tow		
А										WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE							А
	00	04-May-25	y-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.						MATERIAL HIGH-CONDUCTIVITY PRT. NO. WROUGHT COPPER DA2014F NTS						RID ANGLE PI	ROJECTION	
1	REV	DATE	DWN	CHK		DESCRI	PTION		ECN F	ELECTRO TIN PLATE	DWG. NO. 186-cp09	93	nit In	ICH .	(1)		,
			4				3	4	7	2				1			